Slim POS

15.6" Fan-less Touchscreen Terminal Powered by Intel® Processor









Features:

- ♦ High-performance processors: Intel Core™ 12th Gen
- Premium Design: Die-cast aluminum, fanless, ultra-slim.
- Easy Maintenance: Detachable motherboard, HDD, modular.
- User Experience: IPS wide-angle display, foldable stand.
- Customizable Options: Supports MSR, RFID (including under-screen NFC), iButton, and fingerprint modules.
- Expandable Display: Optional 11.6-inch or 15.6-inch secondary screens.

Introduction:

Slim POS is a cutting-edge point-of-sale solution designed to elevate business operations with advanced technology and sleek aesthetics. Engineered for performance, versatility, and ease of use, Slim POS combines powerful hardware with a premium, user-friendly design to meet the demands of modern retail, hospitality, and service environments.

Application:











Specifications:

	Model	GS-J6412	GS-i5	GS-3568
System	CPU	Intel® Celeron® J6412	Intel ® Core™ i5-1235U	RK3568 Quad-core Cortex-
		processor	Processor	A55 up to 2.0GHz
	RAM	8GB Standard, DDR4 2933	8GB Standard, DDR4 3200	2GB Standard, LPDDR4, On-
		MT/s, Socket 1 x SODIMM	MT/s, Socket 1 x SODIMM	board
Storage	SSD	(Max. 32GB) 1. Form Factor: M.2 SATA 2280 (Max to 2TB) 2. Mountable quantity: Up to 2 units can be installed. * Factory Default: M.2 SATA 2280 128G		eMMC 64GB, On-board (Optional 8GB/16GB/32GB/64GB, Max.128GB)
os	Operating Systems	Win 10 / Win 11 / Linux		Android 11/12/13/14
Display	Туре	15.6" LED Backlit LCD Display		
	Resolution	1920 x 1080		
	Brightness	250 cd/m ²		
Touchscreen	Туре	Projected Capacitive Touch		
I/O	Standard I/O	1 x DC_IN 1 x LAN 1 x HDMI 2 x USB3.0 1 x VGA (DB15) 1 x Line-out 1 x Mic_in 2 x USB2.0	1 x DC-IN 1 x HDMI 1 x Type C 1 x LAN 4 x USB 3.0 2 x COM RS232 (RJ48) 1 x Line-out	1 x DC-IN 1 x RJ11(Cash Drawer) 1 x RJ11 1 x LAN 2 x USB 3.0 2 x USB2.0 1 x TF Card slot (max to 32GB) 1 x Line-out
	Buttons	1 x Power On / Off Button		
Options & Peripherals	2nd Displays Customer Display	11.6" (1366 x 768),, 15.6" (1920 x 1080) VFD, 20 Columns x 2 Lines		
	Magnetic Stripe Reade	Comply with ISO 7811, Support 1 & 2 & 3 Track		
	Dallas	Dallas i-button Reader		
	Fingerprint	Yes		
	Combo Reader	MSR+RFID		
	Wall Mount Kit	VESA-Compatible, 75 x 75(mm)		
	Speaker	1 x 2.2W@4Ω max		
	WiFi / BT	Combo Module, WiFi / BT / 3G / 4G		
Power	Adapter	External DC Power Adapter 60W, 12V / 5A		
Mechanical	Dimension	365*205*315mm		